


# Drop Ancillary

## TR75SWS - 75Ω Premium Terminator



Poor electrical terminations caused by moisture migration wreak havoc on system performance. Common faulty 75 Ohm terminations caused by moisture result in service calls. The TR75SWS AquaTight® Drop Terminator terminator guarantees the use of the proper port seal every time, keeping the moisture out, improving network performance and reducing costly service calls.



Specifications	
Return Loss	-30 dB to 3 GHz minimum
Shielding Effectiveness	-120 dB minimum
Corrosion Resistance	meets SCTE and Belcore per ATSM B117 (1000 hour salt fog)
Moisture Migration	Meets SCTE IPS-TP-013 (Red-dye moisture migration test)
<i>Meets or Exceeds all SCTE Specifications</i>	

Specifications for Isolation	
Resistance (electrical)	3.5E+13 Ohm
Isolation Withstand	>5,000 (VDC or VAC)
<i>Meets or Exceeds all SCTE Specifications</i>	

### Related Products



**TR75S**  
Basic Terminator



**PST75WS**  
AquaTight/Locking Terminator



**PST75IWS**  
AquaTight/Locking/Isolation Terminator

*This product may be protected by one or more patents. For further information, please visit: [www.ppc-online.com/patents](http://www.ppc-online.com/patents)*