

Miniflex® Wall Clips



Features & Benefits

- Flame retardant, UV and water resistant polymer (indoor/outdoor)
- High tensile retention
- Cable can be removed and reinstated without clip damage
- Can be fixed to a variety of surfaces
- Distribution/frequency of clips can be greatly reduced
- Supplied with wall fixings and adhesive pad

Compatibility List

- 2 mm and 3 mm Miniflex® Fiber Cable
- PPC QuikPass™ Distribution Cable
- 8mm and 10mm Miniflex Microduct
- QuikPush® Cable Assemblies



Overview

Suitable for indoor and outdoor use, Miniflex Wall Clips are low-profile, easy-to-use fixing accessories designed specifically for a range of Miniflex cables, protection tubes and microducts. Miniflex Wall Clips provide high tensile retention by virtue of the gripping features within the clip which holds onto the Miniflex jacket snugly. This ensures high pull-out resistance and improves the appearance of the installation by preventing the sag associated with traditional cable clips.

The Miniflex clips offer several advantages over traditional cable and conduit clips when securing Miniflex to wall surfaces, including the ability to remove and reinstate the cable without damaging the clip. Supplied in packs of 200 pieces, the clips include the necessary screws and wall fixings as well as self-adhesive pads for application on surfaces that are not suitable for screw mounting.

Applications

- Indoor & Outdoor FTTx Installations
- QuikPass Solution

Technical Data

Part Number	Compatible Miniflex Size	Clip Dimensions (L x H x D)	Tensile Retention
	<i>mm</i>	<i>mm (in)</i>	<i>N</i>
10-1407	2.0	23.0 x 6.4 x 5.1 (0.9 x 0.25 x 0.2)	> 30
10-1408	3.0	19.0 x 7.5 x 5.8 (0.75 x 0.3 x 0.23)	> 40
10-1409	8.0	21.0 x 16.0 x 11.0 (0.83 x 0.63 x 0.43)	> 80
10-1410	10.0	21.0 x 18.0 x 12.9 (0.83 x 0.71 x 0.51)	> 80

This product may be protected by one or more patents • For further information, please visit: www.ppc-online.com/patents

customerservice@ppc-online.com • 1-800-800-6652 • www.ppc-online.com

Miniflex® Wall Clips



Technical Data

Operating Temperature Range	Flame Retardancy	Color
10°C to 50°C (14°F to 122°F)	UL 94: V0	White

Ordering Information

Part Number	Description	Compatible Miniflex Size	Pack Dimensions L x H x D	Pack Quantity
	<i>mm</i>	<i>mm</i>	<i>mm (in)</i>	<i>Pcs</i>
10-1407	2 mm Miniflex® Wall Clip	2.2	185 x 97 x 125 (7.3 x 3.8 x 4.9)	200
10-1408	3 mm Miniflex® Wall Clip	3.0		
10-1409	8 mm Miniflex® Wall Clip	8.0		
10-1410	10 mm Miniflex® Wall Clip	10.0		