PerfectFlex®
BROADBAND COAXIAL CABLE

75 Ohm Coaxial Cable
P6S60VVRF

PPC Innovate. Connect.
A BELDEN BRAND


General Description:
6 Series, Standard Shield, 60% Braid,
Footage Marked, Reel Package

Center Conductor: Copper covered steel
Nominal Diameter: 0.040" (1.02 mm)

Dielectric: Closed cell foamed polyethylene
Nominal Diameter over Dielectric: 0.180" (4.57 mm)

Shield:
1st Shield: APA laminated tape bonded to dielectric
Nominal Diameter over Tape: 0.188" (4.78 mm)
2nd Shield: 34 AWG aluminum braid wire; 60% coverage

Jacket: Black PVC
Nominal Diameter over Jacket: 0.273" (6.93 mm)



Frequency (MHz)	Maximum (dB/100ft)	Maximum (dB/100 m)
5	0.58	1.9
55	1.55	5.09
211	3.00	9.84
250	3.20	10.5
300	3.50	11.48
350	3.80	12.47
400	4.12	13.52
450	4.37	14.34
500	4.63	15.19
550	4.86	15.94
600	5.08	16.67
750	5.65	18.54
870	6.10	20.01
1000	6.54	21.46

NEC Rated: NEC CATV

Electrical Properties:
Impedance: 75 +/- 3 Ohms
Velocity Propogation: 85% Nominal

Cable Length Per Reel: 1,000 ft (305 m)

Shipping Weight: 30lbs/1,000 ft

Packaging: 12"x4"x12" (30.5x10.2x30.5 cm)



Unless otherwise specified, dimensions, material, electrial and mechanical specifications shall comply with ANSI SCTE 74
*Cable image for reference only. Please refer to jacket description for color.

RoHS COMPLIANT LEAD FREE

6176 East Molloy Road - East Syracuse, NY 13057-0278 - Tel: 315-431-7200 - Email: ppc@ppc-online.com - www.ppc-online.com