

PerfectFlex®

BROADBAND COAXIAL CABLE

75 Ohm Coaxial Cable
P11ET77EFORF



A **BELDEN** BRAND

GENERAL DESCRIPTION

11 Series, Perfect Prep®, Tri-shield, 77% Braid, Underground Floodant, Orange PE Jacket, Footage Marked, Reel Package

MECHANICAL SPECIFICATIONS


Center Conductor:	Copper-covered steel
Nominal Diameter:	0.064" (1.63 mm)
Dielectric:	Closed cell foamed polyethylene
Nominal Diameter	0.280" (7.11 mm)

SHIELD

1st Shield	APA-laminated tape bonded to dielectric
Nominal Diameter Over Tape:	0.288" (7.29 mm)
2nd Shield	34 AWG aluminum braid wire; 77% coverage
3rd Shield:	APA-laminated tape bonded to jacket

JACKET

Jacket:	Orange PE, Sunlight Resistant
Nominal Diameter Over Jacket:	0.400" (10.16 mm)



PERFORMANCE SPECIFICATIONS

Attenuation (max corrected to 20°C)

Frequency (MHz)	Maximum (dB/100ft)	Maximum (dB/100m)
5	0.36	1.18
55	0.95	3.12
211	1.81	5.94
250	1.98	6.50
300	2.17	7.12
350	2.36	7.74
400	2.53	8.30
450	2.69	8.83
500	2.85	9.35
550	3.01	9.88
600	3.16	10.37
750	3.58	11.75
870	3.90	12.80
1000	4.23	13.88

PERFORMANCE SPECIFICATIONS

NEC Rated:	None
Characteristic Impedance:	75 +/- 3 Ohms
Nominal Velocity Propagation:	82%



PACKAGING SPECIFICATIONS

Cable Length per Reel:	1,000 ft. (305 m)
Packaging Dimensions:	18" x 6" x 11" (45.7 x 15 x 28 cm)
Shipping Weight per Reel:	55 lbs./1,000 ft.

Unless otherwise specified, dimensions, material, electrical and mechanical specifications shall comply with ANSI SCTE 74
*Cable image for reference only. Please refer to jacket description for color.

This product may be protected by one or more patents • For further information, please visit: www.ppconline.com/patents



6176 East Molloy Road | East Syracuse, NY 13057 | 1-800-800-6652 | ppc@ppc-online.com | www.ppc-online.com