

## GENERAL DESCRIPTION

6 Series, Perfect Prep®, Tri-shield, 77% Braid, Black PVC Jacket, NEC CATVR Rated, Footage Marked, Reel Package

### MECHANICAL SPECIFICATIONS


<b>Center Conductor:</b>	Copper-covered steel
<b>Nominal Diameter:</b>	0.040" (1.02 mm)
<b>Dielectric:</b>	Closed cell foamed polyethylene
<b>Nominal Diameter</b>	0.180" (4.57 mm)

### SHIELD

<b>1<sup>st</sup> Shield</b>	APA-laminated tape bonded to dielectric
<b>Nominal Diameter Over Tape:</b>	0.188" (4.78 mm)
<b>2<sup>nd</sup> Shield</b>	34 AWG aluminum braid wire; 77% coverage
<b>3<sup>rd</sup> Shield:</b>	APA-laminated tape bonded to jacket

### JACKET

<b>Jacket:</b>	Black PVC, Riser Rated
<b>Nominal Diameter Over Jacket:</b>	.278" (7.06 mm)



### PERFORMANCE SPECIFICATIONS

Attenuation (max corrected to 20°C)

Frequency (MHz)	Maximum (dB/100ft)	Maximum (dB/100m)
5	0.58	1.90
55	1.55	5.09
211	3.00	9.84
250	3.20	10.50
300	3.50	11.48
350	3.80	12.47
400	4.12	13.52
450	4.37	14.34
500	4.63	15.19
550	4.86	15.94
600	5.08	16.67
750	5.65	18.54
870	6.10	20.01
1000	6.54	21.46

### PERFORMANCE SPECIFICATIONS

<b>NEC Rated:</b>	NEC CATVR
<b>Characteristic Impedance:</b>	75 +/- 3 Ohms
<b>Velocity Propagation:</b>	85% Nominal



### PACKAGING SPECIFICATIONS

<b>Cable Length per Reel:</b>	1,000 ft. (305 m)
<b>Packaging Dimensions:</b>	12" x 4" x 12" (30.5 x 10 x 30.5 cm)
<b>Shipping Weight per Reel:</b>	33 lbs./1,000 ft.

Unless otherwise specified, dimensions, material, electrical and mechanical specifications shall comply with ANSI SCTE 74  
\*Cable image for reference only. Please refer to jacket description for color.