

# Diamond® Hardware

## Round Drop Clamp



### Features & Benefits

- Shell and wedge made of high-grade aluminum alloy
- Shim made of high strength Acetal
- Tail wire made of high-grade stainless steel
- Mechanical strength of 555 lb (251.7 kg) exceeds yield strength of drop wire
- Suitable for 5 mm – 8 mm MASS/ADSS fiber



### Overview

PPC's Diamond® Fiber Clamp is used to support both ends of an aerial service drop span at the messenger strand and building. The unique, proprietary approach that we have developed for mechanical galvanizing – and the standards we insist on for our raw materials – ensure our Diamond parts can withstand corrosive environments for decades. A long-lasting product is an important factor since replacement costs are so high.

### Ordering Information

PPC Part Number	Box Quantity	Carton Quantity	Weight per 100	Minimum Order Quantity	Order Multiples
23-99991	25	500	6 lb (2.7 kg)	25	25



This product may be protected by one or more patents • For further information, please visit: [www.ppc-online.com/patents](http://www.ppc-online.com/patents)

6176 E. Molloy Rd. East Syracuse, NY 13057 U.S.A. • [customerservice@ppc-online.com](mailto:customerservice@ppc-online.com) • 1-800-800-6652 • +1 315-431-7200 • [www.ppc-online.com](http://www.ppc-online.com)