

QuikPush® Enclosure

Small Customer Terminal



Features & Benefits

- Allows for 100% splice-less FTTH installations
- IP55 protection from dust and water
- Supplied with SC or LC duplex adapter
- Small footprint for minimum decor disruption
- Slack cable storage for up to 2 m (6.5 ft) of 3mm Miniflex® cable
- Large cable entry port for PPC cable or microduct
- Supplied with wall fixings and cable ties

Compatibility

- All PPC and industry standard cable
- QuikPush® cable connector (SC & LC)
- PPC Microduct



Overview

PPC's QuikPush Small Customer Terminal (QP-SCT) is a cost-effective, low-profile termination point for FTTH deployments. The QP-SCT is typically located inside the customer dwelling and connects to the Network Access Point via PPC's pre-terminated QuikPush drop cable. Compatible with SC and LC adapters, the small customer terminal provides the ideal solution for QuikPush cables, with capacity to store up to 2 m (6.5 ft) of slack 3mm Miniflex cable. Suitable for indoor use, the QP-SCT facilitates the use of the pre-terminated PPC QuikPush drop cables within customer dwellings, between the network floor distribution point and the end user's Optical Network Terminal.

Applications

- FTTH
- Multi-dwelling Units
- Premise installations
- Telecommunications

Technical Data

Part Number	Connector Adapter
10-1327	SC/APC
10-1327-U	SC/UPC
10-1327-D	2 x SC/APC
10-1327-DU	2 x SC/UPC
10-1416	Duplex LC/APC
10-1416-U	Duplex LC/UPC
10-1416-D	2 x Duplex LC/APC
10-1416-DU	2 x Duplex LC/UPC

Specification	Unit	Parameter
Dimensions (H x W x D)	mm (in)	86 x 86 x 24 (3.38 x 3.38 x .94)
Weight	kg (oz)	1 (35.3)
Recommended Slack Storage	m (ft)	1 (3.2)
Max Slack Storage	m (ft)	2 (6.5)
Port Diameter	mm (in)	2-10 (5/64-25/64)
Order Pack Quantity	pcs	10
Operating Temp	°C (°F)	-20 to 75 (-4 to 167)