

Miniflex®

Standalone - Riser Microduct



Features & Benefits

- UL 2024 Riser Rated
- Low Smoke Zero Halogen (LSZH)
- Miniflex® technology
- Ultra low friction DVC lining
- High crush resistance
- Best-in-class push/pull and blow-ability
- Tough yet flexible with a small bend radius

Compatibility:

- Industry standard push-fit connectors
- All microduct, fiber and cables



*UL 2024 Riser Communications Raceway File
Number E306979*



Overview

PPC's Miniflex Riser Microduct is a microduct for the routing of optical fiber cable within buildings. It is manufactured with an industry-leading low-friction lining to assist with pulling, blowing and pushing methods of installing cables. The riser microduct fully conforms with the UL 2024 standard for a Riser Communications Raceway and can be used to route any Riser Rated fiber cable.

Miniflex Riser Microduct uses a flame retardant and LSZH polymer; suitable to use indoors. This high-grade polymer, blended with low smoke flame retardants, meets the crucial requirements for in-building use and conforms with the UL 2024 specification for Riser Communications Raceways.

It is a future-proof raceway that enables the fast deployment of fiber as and when it is required, using simple, cost-effective techniques.

Applications

- FTTh/FTTx - Indoor
- Data Infrastructure
- Telecoms

Miniflex®

Standalone - Riser Microduct



Technical Data

Product Specifications

Material	OD	ID	Crush	Tension	Nominal Weight	Bend Radius
	(mm)	(mm)	(n)	(n)	lbs/kft	
PEMX	8.0	5.5	400	250	16.3	20x OD

*This is the minimum radius to which the microduct should be subjected to once it is installed.

Environmental Specification

Operating Temperature	Installation Temperature
°C (°F)	°C (°F)
-40 to 70 (-40 to 158)	-10 to 60 (14 to 140)

Ordering Information

Part Number	Product Code	SKU Length	SKU Weight	Reel Diameter	Reel Weight	Reel Width
		(ft)	(lbs)	(mm)	(lbs)	(mm)
10-0003FT	MD-P-8-5.5-PE-WHT-V0-LSZH-3280FT	3280	77.0	750	14.3	400
10-0008FT	MD-P-8-0-5.5-PE-WHT-V0-LSZH-1000FT	1000	23.5	500	14.3	320

Specifications: ISO9001 Production, REACH, ROHS, Certificate of Origin