



Description: Adaptor, 5/8 female Push On – F female.

DATA SHEET

Electrical

	Specification		Standard	
Frequency Range	5 MHz – 3.000 MHz			
Impedance	75 Ω nominal			
	Better Than	Measured – Worst case of 5 measurements		
Return Loss	34 dB 34 dB 30 dB 19 dB 15 dB 12 dB	\geq 37.3 dB \geq 41.3 dB \geq 33.6 dB \geq 22.4 dB \geq 18.4 dB \geq 15.9 dB	5 MHz – 500 MHz 500 MHz – 860 MHz 860 MHz – 1.000 MHz 1.000 MHz – 1.750 MHz 1.750 MHz – 2.150 MHz 2.150 MHz – 3.000 MHz	IEC 61169-1
Insertion Loss	0.10 dB 0.11 dB 0.11 dB 0.14 dB 0.17 dB 0.25 dB	\leq 0.07 dB \leq 0.08 dB \leq 0.08 dB \leq 0.11 dB \leq 0.14 dB \leq 0.22 dB	5 MHz – 500 MHz 500 MHz – 860 MHz 860 MHz – 1.000 MHz 1.000 MHz – 1.750 MHz 1.750 MHz – 2.150 MHz 2.150 MHz – 3.000 MHz	
Shielding Effectiveness (Measured with CoMeT)	Transfer Impedance @ 5 – 30 MHz \leq 1.04 m Ω /item Screening Attenuation @ 30 – 1.000 MHz \geq 87.4 dB Screening Attenuation @ 1.000 – 2.000 MHz \geq 79.4 dB Screening Attenuation @ 2.000 – 3.000 MHz \geq 72.6 dB Class: A		IEC 62153-4-3 IEC 62153-4-4 IEC 62153-4-4 IEC 62153-4-4 EN 50117	
Common Path Distortion	\leq -110 dBc		ANSI/SCTE 109 2005	
Inner Conductor Resistance	\leq 8 m Ω @ 1 A DC.		IEC 61169-1	
Amp. Rating	\leq 4 A @ 60 V.			
Dielectric Strength	\geq 2 KV.		IEC 61169-1	
Insulation Resistance	\geq 29.99 G Ω @ 500 V.		IEC 61169-1	

Environmental

	Specification	Standard
Temperature range Operating	-40°C to +60°C	
Temperature range Installation	-5°C to +50°C	

Mechanical

	Specification	Standard
Interface	5/8 female (KSF) F female	ANSI/SCTE 91 IEC 61169-24

Material and Finish

	Specification	Standard
Housing	NiSn (NITIN) plated Brass	ASTM B605
Inner conductor	NiSn (NITIN) plated Brass, with Spring Contact	ASTM B605
Insulator	Polyethylene	

In order to continue to supply the best products, PPC reserves the right to change the products and specifications at any time without prior notice.

Measurement setup:

Nm-58f, 58m-58m – **58FPO-FF** – 58m-Fm, Nm-58f.

All results are the worst case result of measurement of 5 assemblies.

All tests are performed using instruments calibrated in accordance to our ISO 9001 certification.

Return Loss, Insertion Loss and Shielding are measured with Rohde & Schwarz ZNB8 Network Analyzer, according to IEC standards.

CPD (Common Path Distortion) are measured with hp Spectrum Analyzer hp 8591E, according to SCTE standard.

In case of over current (≥ 4 A.) there is a risk for high temperature inside the adaptor, which can cause damage of the insulator.

Further test reports, technical specifications and installation instructions can be obtained on request.

