



Description: Extension Adaptor, 5/8 male w. Easy Swivel – 5/8 female length 76 mm. Accept PIN Ø 1.8 mm to 2.0 mm.

DATA SHEET

Electrical

	Specification			Standard
Frequency Range	5 MHz – 3.000 MHz			
Impedance	75 Ω nominal			
Return Loss gated of adaptor	Better Than	Measured	– Worst case of 5 measurements	IEC 61169-1
	37 dB	≥ 40.9 dB	5 MHz – 500 MHz	
	35 dB	≥ 38.2 dB	500 MHz – 860 MHz	
	34 dB	≥ 37.2 dB	860 MHz – 1.000 MHz	
	29 dB	≥ 32.2 dB	1.000 MHz – 1.750 MHz	
	27 dB	≥ 30.6 dB	1.750 MHz – 2.150 MHz	
	25 dB	≥ 28.6 dB	2.150 MHz – 3.000 MHz	
32 dB	≥ 35.5 dB	1.218 MHz		
Insertion Loss	0.13 dB	≤ 0.1 dB	5 MHz – 3.000 MHz	
Shielding Effectiveness (Measured with CoMeT)	Transfer Impedance @ 5 – 30 MHz ≤ 0.11 mΩ/item			IEC 62153-4-3
	Screening Attenuation @ 30 – 1.000 MHz ≥ 123.1 dB			IEC 62153-4-4
	Screening Attenuation @ 1.000 – 2.000 MHz ≥ 123.1 dB			IEC 62153-4-4
	Screening Attenuation @ 2.000 – 3.000 MHz ≥ 116.4 dB			IEC 62153-4-4
Common Path Distortion	Class: A++			EN 50117
Amp. Rating	≤ -110 dBc			ANSI/SCTE 109 2005
Dielectric Strength	≤ 15 A @ 60 V.			
Insulation Resistance	≥ 3 kV.			IEC 61169-1
	≥ 29.99 GΩ @ 500 V.			IEC 61169-1

Environmental

	Specification	Standard
Temperature range Operating	-40°C to +60°C	
Temperature range Installation	-5°C to +50°C	
Sealing Test	IPX8 – 1 meter / 24 hours	IEC 60529
Red Dye		ANSI/SCTE 60
Corrosion Protection		ASTM B 117-94

Mechanical

	Specification	Standard
Interface	5/8 male 5/8 female	ANSI/SCTE 92 ANSI/SCTE 91

Material and Finish

	Specification	Standard
Housing	NiSn (NITIN) plated Brass	ASTM B605
Inner conductor	NiSn (NITIN) plated Brass, with spring contact	ASTM B605
O'ring	EPDM	
Insulator	Polyethylene	

In order to continue to supply the best products, PPC reserves the right to change the products and specifications at any time without prior notice.

Measurement setup:

Nm-58f – **58MES-58FEXT76** – 58m-58m, Nm-58f.

All results are the worst case result of measurement of 5 adaptors.

All tests are performed using instruments calibrated in accordance to our ISO 9001 certification.

Return Loss, Insertion Loss and Shielding are measured with Rohde & Schwarz ZNB8 Network Analyzer, according to IEC standards.

In case of over current (≥ 15 A.) there is a risk for high temperature inside the adaptor, which can cause damage of the insulator.

Further test reports, technical specifications and installation instructions can be obtained on request.

