



Description: Adaptor, 5/8 male to 5/8 male.

## DATA SHEET

### Electrical

	Specification		Standard
Frequency Range	5 MHz – 3.000 MHz		
Impedance	75 Ω nominal		
	Better Than	Measured – Worst case of 5 measurements	
Return Loss	33 dB 33 dB 33 dB 33 dB 31 dB 29 dB	≥ 36.6 dB ≥ 42.0 dB ≥ 45.5 dB ≥ 41.1 dB ≥ 34.7 dB ≥ 32.4 dB	5 MHz – 500 MHz 500 MHz – 860 MHz 860 MHz – 1.000 MHz 1.000 MHz – 1.750 MHz 1.750 MHz – 2.150 MHz 2.150 MHz – 3.000 MHz IEC 61169-1
Insertion Loss	0.13 dB	≤ 0.10 dB	5 MHz – 3.000 MHz
Shielding Effectiveness (Measured with CoMeT)	Transfer Impedance @ 5 – 30 MHz ≤ 0.38 mΩ/item Screening Attenuation @ 30 – 1.000 MHz ≥ 115.9 dB Screening Attenuation @ 1.000 – 2.000 MHz ≥ 113.0 dB Screening Attenuation @ 2.000 – 3.000 MHz ≥ 103.7 dB Class: A++		IEC 62153-4-3 IEC 62153-4-4 IEC 62153-4-4 IEC 62153-4-4 EN 50117
Common Path Distortion	≤ -110 dBc		ANSI/SCTE 109 2005
Amp. Rating	≤ 15 A @ 60 V.		
Dielectric Strength	≥ 3 kV.		IEC 61169-1
Insulation Resistance	≥ 29.99 GΩ @ 500 V.		IEC 61169-1

### Environmental

	Specification	Standard
Temperature range Operating	-40°C to +60°C	
Temperature range Installation	-5°C to +50°C	
Corrosion Protection		ASTM B 117-94

### Mechanical

	Specification	Standard
Interface	5/8 male	ANSI/SCTE 92

### Material and Finish

	Specification	Standard
Housing	NiSn (NITIN) plated Brass	ASTM B605
Inner conductor	NiSn (NITIN) plated Brass	ASTM B605
Insulator	PEHD	

In order to continue to supply the best products, PPC reserves the right to change the products and specifications at any time without prior notice.

**Measurement setup:**

Nm-58f – **58M-58M** – Nm-58f.

All results are the worst case result of measurement of 5 adaptors.

All tests are performed using instruments calibrated in accordance to our ISO 9001 certification.

Return Loss, Insertion Loss and Shielding are measured with Rohde & Schwarz ZNB8 Network Analyzer, according to IEC standards.

CPD (Common Path Distortion) are measured with hp Spectrum Analyzer hp 8591E, according to SCTE standard.

In case of over current ( $\geq 15$  A.) there is a risk for high temperature inside the adaptor, which can cause damage of the insulator.

Further test reports, technical specifications and installation instructions can be obtained on request.

