



Description: Adaptor, BNC female – IEC female.

DATA SHEET

Electrical

	Specification		Standard
Frequency Range	5 MHz – 3.000 MHz		
Impedance	75 Ω nominal		
	Better Than	Measured – Worst case of 5 measurements	
Return Loss	30 dB 29 dB 28 dB 27 dB 26 dB 25 dB	\geq 33.5 dB \geq 32.2 dB \geq 31.8 dB \geq 30.0 dB \geq 29.4 dB \geq 28.8 dB	5 MHz – 500 MHz 500 MHz – 860 MHz 860 MHz – 1.000 MHz 1.000 MHz – 1.750 MHz 1.750 MHz – 2.150 MHz 2.150 MHz – 3.000 MHz IEC 61169-1
Insertion Loss	0.13 dB	\leq 0.1 dB	5 MHz – 3.000 MHz
Shielding Effectiveness (Measured with CoMeT)	Transfer Impedance @ 5 – 30 MHz \leq 0.18 m Ω /item Screening Attenuation @ 30 – 1.000 MHz \geq 114.6 dB Screening Attenuation @ 1.000 – 2.000 MHz \geq 109.4 dB Screening Attenuation @ 2.000 – 3.000 MHz \geq 105.0 dB Class: A++		IEC 62153-4-3 IEC 62153-4-4 IEC 62153-4-4 IEC 62153-4-4 EN 50117
Common Path Distortion	\leq -110 dBc		ANSI/SCTE 109 2005
Amp. Rating	\leq 8 A @ 60 V.		
Dielectric Strength	\geq 3 kV.		IEC 61169-1
Insulation Resistance	\geq 29.99 G Ω @ 500 V.		IEC 61169-1

Environmental

	Specification	Standard
Temperature range Operating	-40°C to +60°C	
Temperature range Installation	-5°C to +50°C	
Corrosion Protection		ASTM B 117-94

Mechanical

	Specification	Standard
Interface	BNC female IEC female	IEC 61169-8 IEC 61169-2

Material and Finish

	Specification	Standard
Housing	NiSn (NITIN) plated Brass	ASTM B605
Inner conductor	NiSn (NITIN) plated Brass	ASTM B605
Spring (IECF)	NiSn (NITIN) plated Beryllium Copper	
Insulator	PEHD	

In order to continue to supply the best products, PPC reserves the right to change the products and specifications at any time without prior notice.

Measurement setup:

Nm-Ff, Fm - 1 m. RG6 cable - BNCm, **BNCF-IECF**, 58m-IECm, Nm-58f.

All results are the worst case result of measurement of 5 adaptors.

All tests are performed using instruments calibrated in accordance to our ISO 9001 certification.

Return Loss, Insertion Loss and Shielding are measured with Rohde & Schwarz ZNB8 Network Analyzer, according to IEC standards.

CPD (Common Path Distortion) are measured with hp Spectrum Analyzer hp 8591E, according to SCTE standard.

In case of over current (≥ 8 A.) there is a risk for high temperature inside the adaptor, which can cause damage of the insulator.

Further test reports, technical specifications and installation instructions can be obtained on request.