



Description: Hardline Connector, B004-5/8 male.  
(Measured with CNA-11T7RB1 Cable.)

### DATA SHEET

#### Electrical

	Specification			Standard
Frequency Range	5 MHz – 3.000 MHz			
Impedance	75 Ω nominal			
	Better Than	Measured – Worst case of 5 measurements		
Return Loss Gated	31 dB	≥ 34.4 dB	5 MHz – 500 MHz	IEC 61169-1
	29 dB	≥ 32.4 dB	500 MHz – 860 MHz	
	28 dB	≥ 31.8 dB	860 MHz – 1.000 MHz	
	26 dB	≥ 29.8 dB	1.000 MHz – 1.750 MHz	
	26 dB	≥ 29.7 dB	1.750 MHz – 2.150 MHz	
	26 dB	≥ 29.8 dB	2.150 MHz – 3.000 MHz	
	28 dB	≥ 31.0 dB	1.218 MHz	
Insertion Loss	0.13 dB	≤ 0.10 dB	5 MHz – 3.000 MHz	
Shielding Effectiveness of B004-58M (Measured with CoMeT)	Transfer Impedance @ 5 – 30 MHz		≤ 0.71 mΩ/item	IEC 62153-4-3
	Screening Attenuation @ 30 – 1.000 MHz		≥ 105.7 dB	IEC 62153-4-4
	Screening Attenuation @ 1.000 – 2.000 MHz		≥ 104.5 dB	IEC 62153-4-4
	Screening Attenuation @ 2.000 – 3.000 MHz		≥ 85.6 dB	IEC 62153-4-4
Common Path Distortion	Class: A++		EN 50117	
Common Path Distortion	≤ -110 dBc			ANSI/SCTE 109 2005
Inner Conductor Resistance	≤ 2.5 mΩ @ 1 A DC.			IEC 61169-1
Amp. Rating	≤ 15 A @ 60 V.			
Dielectric Strength	≥ 3 kV.			IEC 61169-1
Insulation Resistance	≥ 29.99 GΩ @ 500 V.			IEC 61169-1

#### Environmental

	Specification	Standard
Temperature range Operating	-40°C to +65°C	
Temperature range Installation	-5°C to +50°C	
Sealing Test	IPX8 – 1 meter / 24 hours	IEC 60529
Red Dye		ANSI/SCTE 60
Corrosion Protection		ASTM B 117-94

#### Mechanical

	Specification	Standard
Interface	5/8 male	ANSI/SCTE 92
Cable Retention	≥ 30 kgf	ANSI/SCTE 99

#### Material and Finish

	Specification	Standard
Housing	NiSn (NITIN) plated Brass	ASTM B605
Inner conductor	NiSn (NITIN) plated Brass	ASTM B605
Compression ring	NiSn (NITIN) plated Brass	ASTM B605
O'ring	EPDM	
Insulator	Polycarbonate/Polyethylene	

In order to continue to supply the best products, PPC reserves the right to change the products and specifications at any time without prior notice.

### **Measurement setup:**

Nm-58f, B004-58M – Cable – B004-58M, Nm-58f.

All measurements are done with Cable Network CNA-11T7RB1 cable, length 1.0 meter.

All results are the worst case result of measurement of 5 assemblies.

All tests are performed using instruments calibrated in accordance to our ISO 9001 certification.

Return Loss, Insertion Loss and Shielding are measured with Rohde & Schwarz ZNB8 Network Analyzer, according to IEC standards.

CPD (Common Path Distortion) are measured with hp Spectrum Analyzer hp 8591E, according to SCTE standard.

In case of over current ( $\geq 15$  A.) there is a risk for high temperature inside the connector, which can cause damage of the insulator, and / or the cable.

Further test reports, technical specifications and installation instructions can be obtained on request.

