

Splice Closures & Sheath Repair

Bonding & Grounding Hardware - Bond Bars & Braids

Braid and Web Guard Kit



Kit combines 25 feet of Bonding Braid and 25 feet of Web Guard in a convenient two-coil dispenser pack.

Bonding Braid Features:

- Flexible woven braid 7/16" wide made of die cast zinc alloy with zinc plated screws
- Composed of tinned copper strands
- Electrical carrying capacity of solid No. 6 AWG copper conductor
- Easily trimmed to length and punched for connection to a device

Web Guard Features:

- Open web, low density polyethylene protective covering
- Electrically insulates bonding braid or bonding bars from surrounding components
- Permits compound penetration when used in encapsulated splices

Part Number	Description	Inner Pack	Outer Pack	Min Order QTY
C4011	Braid and Web Guard Kit	1	6	6
C4013	Web Guard only 2x25 ft coils	1	6	6

"The C2056 Bond Coin can be used with the C4011 Braid and Web Guard Kit to provide full surface contact to the bond braid placed across the cable opening".

Copper Bond Bar and Insulator Tubing



Copper Bond Bar

Copper Bond Bar Features:

- Tin plated, Solid copper, 1/2" wide bond bar
- Provides effective shield continuity and dependable mechanical bonding
- Alternating hole and elongated slot configuration easily aligns to bond studs
- Will accommodate the base mounting posts of standard 3 pair and 6 pair terminal blocks

Insulator Tubing Features:

- 7/16" width fits easily and snugly over bond bar
- Provides protection against environmental, electrical and mechanical damage
- For use with both copper and aluminum bond bar when encapsulant is not being used



Insulator Tubing

Part Number	Description	Inner Pack	Outer Pack	Min Order QTY
C4079	Bond Bar 25 Ft Roll	1	10	1
C4081	Bond Bar 100 Ft Roll	1	1	1
C4080	Kit with 25 Ft roll, Copper Bond bar and 25 Ft roll, Insulator Tubing	1	10	1