

# 2-Port Optical Subscriber Box



## Features & Benefits

- Two-piece design with integrated fiber management
- Wall mounted with multiple fiber entry/exit points
- Accommodates mechanical or fusion splice protection sleeves
- Shuttered SC or LC adapter interface
- Adapters may protrude or stay behind the shutters
- Integrated port ID label area in the cover
- 2011/65/EU RoHS compliant and halogen free
- White flame retardant ABS plastic



## Overview

The Optical Subscriber Box (OSB-2S) is a small, compact wall-mountable premises fiber interface that provides two or four fiber ports for indoor FTTx applications. This product has built-in fiber management to ensure long-term reliability and transmission of high-speed services. Port shutters provide additional laser light protection.

## Technical Data

Dimensions (H x W x D)	Materials	Compliance
3.4 in x 3.4 in x 1.0 in (86 mm x 86 mm x 25 mm)	Flame Retardant ABS Plastic	Halogen Free 2011/65/EU RoHS

## Ordering Information

Part Number	Description
OSB-2SSA	Optical Subscriber Box 2-port SC-APC with Shutters
OSB-2SSU	Optical Subscriber Box 2-port SC-UPC with Shutters
OSB-2SLA	Optical Subscriber Box 4-port LC-APC with Shutters
OSB-2SLU	Optical Subscriber Box 4-port LC-UPC with Shutters

r1\_11072023