

# Mini Terminal Hand-off Box



## Features & Benefits

- Developed specifically for wireless applications
- Outdoor rated and meets IP67 requirements
- Enclosure utilizes UL94-V0 rated plastic with UV protection
- Corrosion resistant hardware
- Hand hole or panel mountable
- Mounting flanges designed for easy installation and removal
- Integrated slack management clips
- Industry standard LGX panel compatible mounting bracket
- Mounting bracket is adjustable and removable using the included allen wrench
- (2) cable glands that accept cables with a range of .210" [5.3mm] to .334" [8.5mm] diameter
- Cable glands are split design to accommodate pre-terminated fiber assemblies
- Accommodates (2) of PPC's 63MM MUX units



## Overview

PPC's Mini Terminal Hand-off Box is designed to accept industry standard LGX adapter panels and devices used in outdoor environments. The compact form factor of this terminal makes it an ideal choice for small cell fiber connections either inside a pole, on a panel, or in a subsurface application. The easily removable LGX bracket saves time for installation, test, and maintenance compared to similar solutions.

## Technical Data

Dimensions (HxWxD)	Weight	Operating Temperature
8.77 in x 7.8 in x 5.72 in (222.8 mm x 198.1 mm x 145.2 mm)	2.5 lbs (1.13 kg)	-35°F (-37°C) to 185°F (85°C)

## Ordering Information

PPC Part #	Description
E1P1A1B1C0D0NJ1-61	Light gray terminal with LGX bracket, (2) cable glands, slack cable management
E1P2A1B1C0D0NJ1-61	Light gray terminal with LGX bracket, (2) cable glands, slack cable management, LGX mount panel with (6) dual LC adapters
SSE-PMB	Pole mount bracket kit
SSE-SMB	Strand mount bracket kit

These products may be protected by one or more patents • For further information, please visit: [www.ppc-online.com/patents](http://www.ppc-online.com/patents)

6176 E. Molloy Rd. East Syracuse, NY 13057 U.S.A. • [customerservice@ppc-online.com](mailto:customerservice@ppc-online.com) • 1-800-800-6652 • +1 315-431-7200 • [www.ppc-online.com](http://www.ppc-online.com)