


Hardline NexBand™ Connector



Features & Benefits

- Designed for DOCSIS 4.0+ applications
- Fully rated to 3GHz with improved RF performance to 1.2GHz and 1.8GHz
- Trim lengths marked on pin to support extended frequency installations
- Includes all current features of PPC 3-Piece connectors

Mechanical Specifications

Connector	Hex Size <i>(inches)</i>	CC Trim Length (A) <i>(inches)</i>	Cable Retention <i>(lbs)</i>
NXB500P3	15/16	1	500
NXB540QR	1 1/16	1	500
NXB565P3/TX	1 1/16	1	575
NXB625P3	1 1/16	1	600
NXB700P3/TX	1 3/16	1	650
NXB715QR	1 3/16	1	650
NXB750P3	1 3/16	1	700
NXB840P3/TX	1 5/16	1	750
NXB860QR	1 7/16	1 1/16	795
NXB875P3	1 5/16	1	800

Cable Dimensions

Cable Series	Nominal Center Conductor Diameter <i>(inches)</i>	Nominal Sheath I.D. <i>(inches)</i>	Nominal Sheath O.D. <i>(inches)</i>	Diameter Over Jacket <i>(inches)</i>
500P3	0.109	0.452	0.500	0.570
540QR	0.124	0.513	0.540	0.610
565P3/TX	0.129	0.519	0.565	0.635
625P3	0.136	0.563	0.625	0.695
700P3/TX	0.163	0.653	0.703	0.775
715QR	0.166	0.686	0.715	0.785
750P3	0.166	0.678	0.750	0.830
840P3/TX	0.194	0.780	0.840	0.920
860QR	0.203	0.828	0.860	0.960
875P3	0.194	0.797	0.875	0.955

Preparation & Installation Tools

Two (2) adjustable wrenches


Linemen's pliers or other appropriate cutters

Appropriate cable preparation tools

Electrical Specifications

Bandwidth	0 MHz to 3 GHz
Impedance	75 Ohms (nominal)
Return Loss	-25 dB to 3 GHz
Insertion Loss	-0.25 dB to 3GHz
Operating Voltage	90 V (at 60 Hz continuous AC)
Operating Current Rating	20 Amps (at 60 Hz continuous AC)
Operating Temperature	-40°F to + 140°F (-40°C to 60°C)

Meets or Exceeds all SCTE Specifications



Please contact your PPC Sales representative about future availability

These products may be protected by one or more patents • For further information, please visit: www.ppc-online.com/patents

6176 E. Molloy Rd. East Syracuse, NY 13057 U.S.A. • customerservice@ppc-online.com • 1-800-800-6652 • +1 315-431-7200 • www.ppc-online.com