

General Description:

6 Series, Perfect Prep™, Tri-shield, 77% Braid, Footage Marked, Coil Package

Center Conductor: Copper covered steel

Nominal Diameter: 0.040" (1.02 mm)

Dielectric: Closed cell foamed polyethylene

Nominal Diameter over Dielectric: 0.180" (4.57 mm)

Shield:

1st Shield: APA laminated tape bonded to dielectric


Nominal Diameter over Tape: 0.188" (4.78 mm)

2nd Shield: 34 AWG aluminum braid wire; 77% coverage

3rd Shield: APA laminated tape

Jacket: Black PVC

Nominal Diameter over Jacket: 0.278" (7.06 mm)



Frequency (MHz)	Maximum (dB/100ft)	Maximum (dB/100 m)
5	0.58	1.9
55	1.55	5.09
211	3.00	9.84
250	3.20	10.5
300	3.50	11.48
350	3.80	12.47
400	4.12	13.52
450	4.37	14.34
500	4.63	15.19
550	4.86	15.94
600	5.08	16.67
750	5.65	18.54
870	6.10	20.01
1000	6.54	21.46

NEC Rated: NEC CATV

Electrical Properties:

Impedance: 75 +/- 3 Ohms

Velocity Propogation: 85% Nominal

Cable Length Per Coil: 500 ft (152 m)

Shipping Weight: 33lbs/1,000 ft

Packaging: 10.5"x3.5"x6.9" (26.7x8.9x17.5 cm)

Unless otherwise specified, dimensions, material, electrical and mechanical specifications shall comply with ANSI SCTE 74

*Cable image for reference only. Please refer to jacket description for color.

