

Demarcation Enclosure

Model PHB1094XX



Features & Benefits

- Weather-resistant thermoplastic housing
- Removable in x 2 in section for covering unsightly installations
- Open-ended cable ports for easier and faster installations
- Ergonomically designed internal mounting boss layout
- Custom logo (optional)



Overview

PPC's PHB1094xx demarcation enclosure provides a secure compartment for terminating coaxial cables and mounting any combination of drop components. The enclosure's removable hinged lid has a section that allows for the display of your company's logo. The enclosure can be safeguarded three different ways: two side snap latches, zip-tie/pad lock or locking F-terminator. The internal mounting arrangement allows for a standardized method of installing coax drop components. All mounts are the same height and spaced in 1/2 in increments per SCTE requirements.


To help cover unsightly cable portals and/or components on the side of a home, the back of the enclosure incorporates several 2 in x 2 in sections that can easily be removed via a pull-tab. The open-ended, self-sealing, cable ports at the bottom of the box allow components to be assembled outside of the enclosure making for quicker installations.

Technical Data

UV Resistance	Salt Fog	Chemical Resistance	Material
30 days per ASTM G26-93	60 days per ASTM B117-90	30 Days at 100°F and 95% RH Resists chipping and/or cracking when subjected to household chemicals	Copolymer Impact Polypropylene
Dimensions External (HxWxD)		Dimensions Internal (HxWxD)	
<i>in (mm)</i>		<i>in (mm)</i>	
10 x 9 x 3.5 (254 x 228.6 x 82.6)		11.1 x 11.75 x 5.25 (281.94 x 298.45 x 133.35)	

Ordering Information

PPC Part Number	Description
PHB1094xx	Demarcation Enclosure



This product may be protected by one or more patents • For further information, please visit: www.ppc-online.com/patents

customerservice@ppc-online.com • 1-800-800-6652 • www.ppc-online.com