

Fiber Management Slotted Multi Bracket



The PPC Slotted Multi Bracket (SMB) is used at distribution points where orderly fiber management and protection is required. It provides isolation from tensile loads for vulnerable and sensitive components.

The SMB can be adapted to individual needs with the use of Miniflex™ Protection Tubing (OFPT). From the initial fiber entry to the final termination point, superior fiber protection against bending, crushing and kinking is provided. Assembly of fiber tubes is made easy by a simple lay-through design; no threading is required.

For Ø5mm Miniflex™ a 3 tube and 12 tube bracket is available. for Ø3mm Miniflex™ a 12 tube bracket is offered, each version supporting up to 70N pull on any patch cord to complete the integrity of the system.

**The 3 tube Multi Bracket for Ø5mm is a modular build, clip together unit, for any number of tubes.
The 12 tube Multi Bracket for Ø3mm can be stacked for any number of tubes.**



Advantages

- Isolates tensile loads from vulnerable connectors
- Can be fixed with screws or push rivets
- Minimum of 70N pull out force
- Tube retention cable ties can be utilized
- Ridged to slot Miniflex firmly into place
- Available for Ø3mm and Ø5mm Miniflex™

Compatibility List

- 3mm and 5mm Miniflex™ Tube and Cable

Applications

- Data centers
- Equipment racks and distribution frames
- Premise installations
- Telecommunications



Fiber Management Slotted Multi Bracket



Multi Bracket Material Information

Part #	Part	Material	Properties	Best For	Dimensions	No. of slots
10-0422	12 x 3mm Bag of 100	Nylon	Flame Retardant	Indoor (FR)	5.3(h) x 16.8(w) x 95.8(l) mm	12
10-0289	3 x 5mm Bag of 10	Nylon	Flame Retardant	Indoor (FR)	20(h) x 14.5(w) x 25(l) mm	1
10-1058	12 x 5mm Bag of 10	Nylon	Flame Retardant	Indoor (FR)	20(h) x 25(w) x 40(l) mm	4

Contact

World Headquarters: 6176 E. Molloy Rd. East Syracuse, NY 13057 U.S.A.
Email: customerservice@ppc-online.com Tel: +1 315-431-7200 Toll Free: 1-800-800-6652