

# Pre-terminated Outlet, PTO DIN Rail



## Features & Benefits

- Material: Thermoplastic, halogen-free plastic (ABS)
- Color: pure white (RAL 9010).
- Compatible with G657.A2 fiber
- 1 to 2 adapters
- 1 label strip (45 x 10 mm)
- Protection class / shockproof: IP30 / IK05
- 2 trays for the fibres
- Colour code to identify the ports
- Fire resistance: UL94 V0
- Delivery content: 2 x cable ties, 1 x assembly instructions
- Laser Symbol



## Overview

The PTO DIN rail outlet for terminating up to 4 singlemode fibers was developed for subscriber connection in FTTH projects and is compatible with DIN rails according to DIN.

Thus they offer a simple and fast assembly in new distributions and can also be easily integrated into existing installations.

The FTTH Drop Cable can be terminated in the adapters with various types of connectors.

## Application Image



# Pre-terminated Outlet, PTO DIN Rail



## Ordering Information

Example

PTOF	5	5	4	6	9	3	1	4	1	2	4	1	5	0
	1	2	3	4	5	6	7	8	9					

### 1 Adapter Type

10 = LC Duplex Blue Flangeless  
 11 = LC Duplex Green Flangeless  
 30 = SC Simplex Blue Flangeless  
 31 = SC Simplex Green Flangeless  
 51 = LC Duplex Blue Internal Shutter Flangeless  
 52 = LC Duplex Green Internal Shutter Flangeless  
 55 = SC Simplex Blue Internal Shutter Flangeless  
 56 = SC Simplex Green Internal Shutter Flangeless

### 2 Adapter Quantity

1 = 1  
 2 = 2

### 3 Cable Type

52 = 2F Indoor G657.A1  
 53 = 4F Indoor G657.A1  
 54 = Mibniflex® 2F 2mm G657.A1  
 55 = Miniflex 4F 2mm G657.A1  
 56 = Miniflex 2F 3mm G657.A1  
 57 = Miniflex 4F 3mm G657.A1  
 66 = 2F Indoor G657.A2  
 67 = 4F Indoor G657.A2  
 68 = Miniflex 2F 2mm G657.A2  
 69 = Miniflex 4F 2mm G657.A2  
 70 = Miniflex 2F 3mm G657.A2  
 71 = Miniflex 4F 3mm G657.A2

### 4 Connector Outlet

11 = LC/UPC Simplex  
 12 = LC/APC Simplex  
 31 = SC/UPC Simplex  
 32 = SC/APC Simplex

### 5 Connector Quantity Outlet

1 = 1  
 2 = 2  
 3 = 3  
 4 = 4

### 6 Connector Pulling End

00 = No connector  
 11 = LC/UPC Simplex  
 12 = LC/APC Simplex  
 31 = SC/UPC Simplex  
 32 = SC/APC Simplex  
 82 = SC UPC Balistix (1F Only)  
 83 = SC APC Balistix (1F Only)  
 84 = LC UPC Blow-In Connector  
 85 = LC APC Blow-In Connector  
 86 = SC UPC Blow-In Connector  
 87 = SC APC Blow-In Connector  
 88 = LC UPC Balistix (1F Only)  
 89 = LC APC Balistix (1F Only)

### 7 Connector Quantity Pulling End

See Connector Quantity Outlet (5.)

### 8 Pull-in Loop

1 = Yes  
 2 = No

### 9 Product Length

05 = 5 Meters  
 10 = 10 Meters  
 50 = 50 Meters