

XPON ONT Beam 1K00X



Features & Benefits

- Dual mode ONT (GPON and EPON)
- Compliant with G984.2 & IEEE 802.3ah
- Plug-and-play
- 1 Gigabit port
- ONU Auto discovery



Overview

PPC's XPON Optical Network Terminal (ONT) can be used in applications ranging from residential units to enterprise solutions or to deliver triple-play services to the subscriber in FTTx applications. The GPON HGU (Home Gateway Unit) incorporates interoperability, key customer specific requirements, scalability and cost efficiency. Equipped with ITU-T G.984 compliant 2.5G Downstream and 1.25G Upstream GPON interface, this device supports triple-play services including voice and high-speed internet access service. It's highly reliable and easy to maintain, with guaranteed QoS for different service.

The ONT is fully compliant with GPON and EPON technical regulations such as ITU-T G.984.x, IEEE802.3ah and technical requirement of EPON Equipment. Its dual mode HGU can detect and exchange PON mode automatically. Compliant with standard OMCI definition, this device is manageable at remote side and supports the full range FCAPS functions including supervision, monitoring and maintenance. This ONT can act as a wire-speed L2 switch and L3 routing gateway with functions including port forwarding, NAT, NAPT, and PPPoE clients provide services. This model of ONT is equipped with one Uplink GPON and 1 Gigabit LAN Ethernet.

Technical Data

Interface

Specification	Value
PON interface	1*GPON port, FSAN G.984.2 standard, Class B+
	Downstream Data Rate: 2.488Gbps
	Upstream Data Rate: 1.244Gbps
	SC/APC single-mode fiber
	27dB Link loss and 20KM distance with 1:128 split ratio
Ethernet Interface	1*10/100/1000M auto-negotiation
	Full/half duplex mode
	RJ45 connector
	Auto MDI/MDI-X
	100m distance
Power Interface	12V 0.5A DC Power supply
	2-PIN power adapter input
	Power switch
	Power consumption: less than 10W

This product may be protected by one or more patents • For further information, please visit: www.ppc-online.com/patents

XPON ONT Beam 1K00X



Technical Data

Performance Parameter

Specification	Value
PON Optical Parameter	Wavelength: Tx 1310nm, Rx1490nm
	Tx Optical Power: 0.5~5dBm
	Rx Sensitivity: -27dBm
	Saturation Optical Power: -11dBm
Data Transmission Parameter	PON Throughput: Downstream 2.488Gbit/s s; Upstream 1.244Gbit/s
	Ethernet: 1000Mbps
	Packet Loss Ratio: <1*10E-12
	latency: <1.5ms
Switching Parameters	Ethernet port auto negotiation or manual configuration
	MDI/MDIX automatically sense
	Hardware priority queues on the downstream direction in support of CoS
	802.1D bridging
	VLAN tagging/detagging per Ethernet port
	VLAN stacking (Q-in-Q) and VLAN Translation
	IP ToS/DSCP to 802.1p mapping
	Class of Service based on UNI, VLAN-ID, 802.1p bit, and combination
	Marking/remarking of 802.1p
	IGMP v2/v3 snooping and IGMP snooping with proxy report
	Broadcast/Multicast rate limiting
	Multiple WAN interfaces supporting
	WAN connection <ul style="list-style-type: none"> • Point-to-Point Protocol over Ethernet (PPPoE) • Dynamic Host Configuration Protocol (DHCP) • Static
	DHCP server for LAN devices
	DNS relay
	Network Address Translation (NAT) / Network Address Port Translation (NAPT)
	Port forwarding
	Static routing
Traffic classification and QoS based on Layer 3 and Layer 4 Identifier	
Access Control List (ACL)	
Switching Parameters	VPN Pass thru for Point to Point Tunneling Protocol (PPTP), Layer 2 Tunneling Protocol (L2TP) and IP Security Protocol (IPSec)
	Firewall
	Application Layer Gateway (ALG)
	Demilitarized Zone (DMZ)
	Dynamic Domain Name Server (DDNS)
	Network Time Protocol (NTP)
	Universal Plug and Play (uPnP)
	IGMP proxy
	IPv6 <ul style="list-style-type: none"> • Stateless Address Autoconfiguration (SLAAC) • DHCPv6 • PPPoEv6 • DNSv6

This product may be protected by one or more patents • For further information, please visit: www.ppc-online.com/patents

XPON ONT Beam 1K00X



Technical Data

Standard Protocols

Specification	Value
PON Protocols	ITU-T Recommendation G.984.x (GPON)
	ITU-T Recommendation G.988 (OMCI)
	Advanced Encryption Standard (AES)
	Forward Error Correction (FEC)
	Class B+ optics (28dB)
	T-CONTs: 32
	Logical Range: 60 km
	Max Transmission Distance: 20 km
	GEM Port-IDs: 255;

Device Management

Specification	Value
Management mode	Standard compliant OMCI interface as defined by ITU-T G.984.4
	Standard compliant OMCI (the embedded operations channel) interface as defined by ITU-T G.988
Management Function	Status monitor, Configuration management, Alarm management, Log management

Physical Features & Environmental Conditions

Specification	Value
Dimension (Wx D x H)	90 mm x 73 mm x 25.2 mm
Weight	150 g
Operating Temperature	0 °C to 55 °C (32 °F to 131 °F)
Operating Humidity	5% ~ 95% (non-condensing)
Storage Temperature	-30 °C to 85 °C (-22 °F to 185 °F)
Storage Humidity	5% ~ 95% (non-condensing)
Mounting Option	Desktop & Wall mounting
LED	Power, PON, LOS, LAN

Ordering Information

Part Number	Description
1K00X	XPON ONT 1GE