

Fibre optic termination point (FO-TP) Keystone, flush-mounted



Features & Benefits

- Suitable for flush-mounted installation as well as for installation in wall ducts
- Angled outlet
- Simple mounting and removal
- Few, easily separable housing parts
- Switch ranges
- No visible fasteners, screw concealed by labelling field
- Compliant with RoHS II (2011/65/EC) and REACH (1907/2006)



Overview

The PPC fibre optic termination point Keystone is practical, easy to install and can be integrated into all common installation or underfloor systems. The unpopulated box offers up to 3 x Keystone module receptacles. The box consists of a few, easily separable housing parts.

Mechanical Data

Support ring	Central plate	Colour
Zinc die-cast	ABS plastic, 50x50mm with Labelling field	pure white

Ordering Information

Description	Part Number
Termination Point Keystone 1-fold, FM, empty box, incl. dust protection flaps and labelling field, pure white, PU=10	503005001
Termination Point Keystone 2-fold, FM, empty box, incl. dust protection flaps and labelling field, pure white, PU=10	503005002
Termination Point Keystone 3-fold, FM, empty box, incl. dust protection flaps and labelling field, pure white, PU=10	503005003

Accessories

Description	Part Number
Cover frame 80x80 mm, 1-fold, pure white RAL 9010	524511802-WS
Surface-mounted box incl. cover frame 80x80mm, RAL 9010	524511702-WS
Keystone-Module E-2000 APC, Singlemode	522014033-7035
Keystone-Module LC, Singlemode	522014012-7035
Keystone-Module SC, Singlemode	522014021-7035
Keystone-Module SC APC, Singlemode	522014021-7035-GN